



表226 : RBSMA(C10 class)シリーズ寸法表 (標準, 中リード)

単位 : mm

型番	加工区分	呼び		ネジ軸 谷径 d ₁	ナット主要寸法								ボール径 D _w	循環数	基本定格荷重		最大ネジ軸長 L ₀
		外径 d	リード ℓ		D	L _t	D _f	T	W	PCD	X	E			Ca (kN)	Coa (kN)	
RBSMA0802	R	8	2	6.6	20	28	40	6	24	30	4.5	—	1.588	3.5×1	1.8	3.2	400
RBSMA1004	R	10	4	7.8	26	34	46	8	28	36	4.5	—	2.381	2.5×1	2.3	4.8	600
RBSMA1204	R	12	4	10.0	30	35	50	8	30	40	4.5	—	2.381	2.5×1	2.6	5.8	800
RBSMA1210	R		10	9.6		44	54	12	32	41	5.5	5	3.175	1.5×1	2.9	5.0	
RBSMA1505	R	15	5	12.5	34	40	54	10	34	44	4.5	5	3.175	2.5×1	5.1	10.5	1200
RBSMA1510	R		10			52	57			45	5.5				5.1	10.5	
RBSMA2005	R	20	5	17.5	40	40	60	10	40	50	4.5	5	3.175	2.5×1	6.2	14.7	2000
RBSMA2010	R		10	16.3	52	57	82	12	52	67	6.6				4.762	10.6	
RBSMA2505	R	25	5	21.8	43	40	67	10	43	55	5.5	5	3.175	2.5×1	6.5	18.7	2500
RBSMA2510	R		10	20.3	60	92	96	15	60	78	9				6.35	2.5×2	
RBSMA2806	R	28	6	25.6	50	65	80	12	50	65	6.6	6	3.175	2.5×2	12.1	42.3	2500
RBSMA3210	R	32	10	27.2	67	92	103	15	67	85	9	5	6.35	2.5×2	32.8	86.7	3000
RBSMA3610	R	36	10	31.1	93	70	110	17	70	90	11	7	6.35	2.5×2	35.1	98.2	3000
RBSMA3620	R		20		89										35.1	98.2	
RBSMA4010	R	40	10	35.1	76	93	116	17	76	96	11	7	6.35	2.5×2	37.1	105.6	4000

* R : 転造品

呼び番号 ボールネジ型番
RBSMA20 05 × 1000
 ネジ軸外径 リード ネジ軸長さ