




表285 : SFSシリーズ寸法表

型番	軸径 d	リード ℓ	主 要			
			h	W	L	Lo
SFS-0825	8	2.5	14.5	28.4	41.1	57.2
SFS-0815	8	15	19.3	38.1	50.8	71.4
SFS-1215	12	15	19.3	38.1	50.8	71.4
SFS-1225	12	25	19.3	38.1	50.8	71.4
SFS-1615	16	15	25.6	50.8	63.5	85.8
SFS-1625	16	25	25.6	50.8	63.5	85.8
SFS-2525	25	25	38.1	76.2	63.5	90.4
SFS-4010	40	10	57.2	114.3	69.9	118.9
SFS-5050	50	50	57.2	114.3	69.9	118.9



SFS-08~16



SFS-25~50

単位 : mm

寸 法					定格スラスト荷重	基本動定格荷重	質 量
H	Ho	w	f	S	Fa (N)	C (N)	(kg)
29	42.2	—	19	M3×0.5 深サ 6	20	150	0.15
38.6	48.5	—	25.4	M5×0.8 深サ 9	130	490	0.25
38.6	48.5	—	25.4	M5×0.8 深サ 9	130	490	0.25
38.6	48.5	—	25.4	M5×0.8 深サ 9	130	490	0.25
51.3	68.3	—	31.8	M6×1.0 深サ12	270	980	0.50
51.3	68.3	—	31.8	M6×1.0 深サ12	270	980	0.50
76.2	88.9	63.5	38	M6×1.0 深サ12	450	1960	1.05
114.3	118.9	101.6	38	M6×1.0 深サ12	880	3430	2.70
114.3	118.9	101.6	38	M6×1.0 深サ12	880	3430	2.70

* Ho : スラスト荷重が無い場合